

040759- SERCO 1050XR 22' BOOM - RANGE/LIFT DIAGRAM

CAPACITIES SHOWN ARE MAXIMUM THEORETICAL LIFT CAPACITIES (LESS ATTACHMENT) BASED ON LOADER SYSTEM PRESSURE INDICATED. LOADERS IS MOUNTED ON ADEQUATELY SIZED VEHICLE, STABILIZERS DEPLOYED IN DOWN POSITION AND THE ENTIRE UNIT IS ON FIRM, LEVEL GROUND. IT IS HIGHLY RECOMENDED THAT PRIOR TO INSTALLATION OF THIS LOADER ONTO TRUCK THAT A STABILITY CALCULATION OR TEST BE PERFORMED TO ENSURE PROPER STABILITY AND OPERATION OF LOADER ON CUSTOMER VEHICLE.

2500 PSI MAIN CYL. OPERATING PRESSURE
 2500 PSI MAIN CYL. RELIEF SETTING
 2500 PSI JIB CYL. OPERATING PRESSURE
 3000 PSI JIB CYL. RELIEF SETTING (BORE & ROD SIDE)

5013461 - MAIN BOOM(12')
 5000915 - JIB BOOM(10')
 6.0" MAIN BOOM CYL
 5.0" JIB CYL

