

040772 - SERCO 160 25' - RANGE/LIFT DIAGRAM

CAPACITIES SHOWN ARE MAXIMUM THEORETICAL LIFT CAPACITIES (LESS ATTACHMENT) BASED ON LOADER SYSTEM PRESSURE INDICATED. LOADER IS MOUNTED ON ADEQUATELY SIZED VEHICLE, STABILIZERS DEPLOYED IN DOWN POSITION AND THE ENTIRE UNIT IS ON FIRM, LEVEL GROUND. IT IS HIGHLY RECOMENDED THAT PRIOR TO INSTALLATION OF THIS LOADER ONTO TRUCK THAT A STABILITY CALCULATION OR TEST BE PERFORMED TO ENSURE PROPER STABILITY AND OPERATION OF LOADER ON CUSTOMER VEHICLE.

2450 PSI MAIN CYLINDER OPERATING PRESSURE
 2500 PSI MAIN CYLINDER RELIEF SETTING
 2450 PSI JIB CYLINDER OPERATING PRESSURE
 3000 PSI JIB CYLINDER RELIEF SETTING (BORE & ROD SIDE)

5002697- MAIN BOOM (14')
 7.0" MAIN CYLINDER
 5005844 - JIB BOOM (11')
 6.0" JIB CYLINDER

