



Bypass Slasher Grapple- SSG Models

Serco Slasher Grapples Are Designed To Handle Tree Length & Are Often Used In Coordination With Our Slasher Cutting Machine To Streamline Logging Processes. Our Multi-Purpose Attachment Is Also Excellent Solutions For a Variety Of Other Logging Applications.



	SSG069- 1/3	SSG068-1/3	SSG065- 1/3	SSG074-1/3	SSG069-5/8	SSG069-5/8 BB
Max. Opening in (mm)	69 (1,760)	68 (1,727)	65 (1,656)	74.25 (1,886)	69.5 (1,765)	69.5 (1,765)
Min. Opening in (mm)	8 (198)	8.75 (222)	8.5 (213)	5 (132)	7 (175.25)	7 (175.25)
Area Tip-To-Tip ft. ² (m ²)	4.19 (0.39)	4.2 (0.39)	6.28 (0.58)	5.85 (0.54)	7.55 (.07)	7.55 (0.7)
Volume in Cord 8ft. (m²)	0.26 (0.94)	0.26 (0.95)	0.39 (1.42)	0.37 (1.33)	0.47 (1.71)	0.47 (1.71)
Cylinder Size in (mm)	3.5 (89)	3.5 (89)	3.5 (89)	3.5 (89)	3.5 (89)	3.5 (89)
Cylinder Max. Pressure PSI (bar)	3,375 (233)	3,375 (233)	4,650 (321)	3,375 (233)	4,650 (321)	4,650 (321)
Weight lb (kg)	1,000 (454)	1,065 (483)	1,130 (513)	1,313 (596)	1,626 (738)	1,798 (816)
Continous Rotation	Yes	Yes	Yes	Yes	Yes	Yes
Dealer Reference Number	680954	5017540	680986	680959	5013966	5017894

Legend:

BB- Bangbaord- Used For Tapping Wood To Straighten Piles. Bangboards Are Built Into The Grapple Arms Or Separate Bangboard Plates.

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS AND TO IMPROVE OUR PRODUCTS WITHOUT NOTICE OR OBLIGATION.





