

Log Grapple- SLG Models

Staple For Loggers. Serco Log Grapples Are Built Tough For The High Demands Of Forestry Applications For Which They Encounter.



	SLG035	SLG042	SLG042-LL	SLG046	SLG052-LBC
Max. Opening in (mm)	35.25 (895)	42 (1,072)	42 (1,072)	46.5 (1,181)	52 (1,323)
Min. Opening in (mm)	3.5 (89)	3.75 (95)	3.75 (95)	5.7 (145)	5.95 (151)
Area Tip-To-Tip ft. ² (m ²)	1.28 (0.12)	2.7 (0.25)	2.7 (0.25)	2.59 (0.24)	4.45 (0.41)
Volume in Cord 8ft. (m ²)	0.08 (0.29)	0.17 (0.62)	0.17 (0.61)	0.16 (0.58)	0.28 (1.01)
Cylinder Size in (mm)	3.5 (89)	3.5 (89)	3.5 (89)	3.5 (89)	4 (102)
Cylinder Max. Pressure PSI (bar)	3,375 (233)	2,900 (199.5)	2,900 (199.5)	3,375 (233)	4,200 (290)
Weight lb (kg)	650 (295)	900 (408)	839 (381)	780 (354)	1,920 (871)
Continous Rotation	Yes	Yes	Yes	Yes	Yes
Dealer Reference	5011004	680998	5009948	680934	680979

Legend:

LL: Load Locks- Prevent Grapple Arms From Opening In Case Of Hydraulic Failure.

LBC: Large Bearing Continuous- Rotator Utilizing Turntable Bearing, Hydraulic Motor & Manifold To Provide Unlimited Rotation (20 1/2" Diameter).

WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS AND TO IMPROVE OUR PRODUCTS WITHOUT NOTICE OR OBLIGATION.